


DYNAMIC



TECHNICAL SPECIFICATIONS


| | |
|---------------------------------|-------------------------------------|
| Product Range | Dynamic |
| Product Description | Tufted Multi-Level Loop Carpet Tile |
| Yarn / Fibre | 100% Solution Dyed Nylon |
| Machine Gauge | 1/12th |
| Pile Height | 4mm +/-0.5mm |
| Total Thickness | 7mm +/-0.5mm |
| Tile Size | 50cm x 50cm |
| Backing Structure | PVC with Recycled Content |
| Tile Installation Method | Quarter Turn, Brick, Ashlar |

SUSTAINABILITY SPECIFICATIONS

| | |
|----------------------------|--|
| Less Waste | Modular carpet creates 85 – 90% less waste than broadloom carpet |
| Product Stewardship | 100% take back & repurpose through accredited partner |
| Recycled Content | Minimum of 55% recycled content in the backing structure Average of 40% recycled content by weight of product |

PERFORMANCE SPECIFICATIONS

| | |
|-------------------------------|--|
| Area of Use | Commercial |
| Dimensional Stability | Less than 0.2% variation |
| Biocontaminant Control | Ultra Fresh Anti-microbial treated |
| Anti-Static | AATCC134 < 3000 Volts |
| Warranty | 15 year limited warranty: • Manufacturing defect • Dimensional stability • Electrostatic propensity |



Specifications are subject to and may change without notice.
Colour variation may occur between sample and production due to dye lot tolerances.