## **Technical Data Sheet**

**Product Specifications** 



**Classic Estate** 



| Product Details                                       |  |                                 |  |
|---|--|---------------------------------|--|
| Technical Data  |  | Technical Data                  |  |
| Туре  | Laminate   | Colours                         | 10   |
| Total Thickness                                       | 12mm   | Construction                    | HDF  |
| Wear Layer  | Melamine Resin   |                                 |  |
| Dimensions  | 1286mm (L) x 194mm (W)   | Surface                         | Emboss in register                               |
| Planks per Box  | 6  | Profile                         | 4-side Bevelled Edge                             |
| M² per Box  | 1.496m²  | M² per Pallet                   | 77.792 m²  |
| Weight per Box  | 17.2 kg  | Installation Method             | Glue-free, Patented Megaloc Click locking system |
| Performance   |  |                                 |  |
| Wear resistance                                       | AC4 / Class 23, 32   |                                 | DIN EN 13329                                     |
| Impact resistance                                     | IC2  |                                 | EN 13329   |
| Resistance to staining                                | Group 1,2: Class 5 Group 3: Class 4                                  |                                 | EN 438   |
| Surface soundness                                     | ≥ 1.25 N/mm²   |                                 | EN 311   |
| Impact Sound Insulation Rating Impact Sound Reduction | L'nT,w = 48<br>Δ L'nT,w = 26dB                                       | 230mm concrete slab & Timbermax | AS/NZS ISO140.7:2006                             |
| Light fastness  | Grey Scale Level ≥ 4   |                                 | EN 20105-A02                                     |
| Residual indentation                                  | ≤ 0.05mm   |                                 | EN ISO 24343-1                                   |
| Furniture Leg movement                                | No Damage with type 0  |                                 | EN 424   |
| Castor Chair resistance                               | No Damage with type W after 25000 c                                  | cycles                          | EN 425   |
| Locking strength                                      | F $_{10.2} \ge 1.0 \text{ kN/m}$<br>F $_{80.2} \ge 2.0 \text{ kN/m}$ |                                 | EN 24334   |
| Reaction to fire                                      | Critical Radiant Flux ≥ 4.5 kW/m2<br>Smoke Value ≤ 750 %.min         | Conforms for all BCA Buildings  | AS/ISO 9239.1-2003                               |
| Slip resistance                                       | P1, R9   |                                 | AS/NZ 4586-2013                                  |
| Formaldehyde  | < 0.1%   | E1 (not detected)               | EN 717-1   |
| Thermal resistance                                    | $R \le 0.15  (m^2 K) / W$  |                                 | EN 12667   |
| Commercial Warranty                                   | 10 Years   |                                 |  |
| Residential Warranty                                  | 25 Years   |                                 |  |
| Sustainability  |  |                                 |  |



**VOC** Rating





E1 compliant for VOC emission rate limits







All specifications and colourations are subject to normal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All product is manufactured under a management system certified as complying with ISO9001 & ISO14001. Airstep Flooring products must be installed in accordance with relevant Australian Standards and in conjuction with the Airstep Flooring Installation Instructions.

Airstep Flooring reserves the right to change the specifications or delete colours on this product without notice. Test results and certificates are available on request. Warranty terms and conditions apply.

For Installation Instructions, Cleaning, Care & Maintenance Instructions, see www.airstepflooring.com.au