Technical Data Sheet

Product Specifications



VINYL PLANK

Product Details				
Technical Data			Technical Data	
Туре	Luxury Vinyl Plank		Colours	12
Total Thickness	3.0mm		Protective Coating	PU Coating
Wear Layer	0.50mm		Finish	Phthalate Free
Dimensions	1219.2mm (L) x 177.8mm (W)		Surface	Woodgrain – Semi Wild
Planks per Box	15		Profile	Square Edge
M² per Box	3.26 m ²		M² per Pallet	179.30 m²
Weight per Box	16.5kg		Installation Method	Glue down – Refer to Installation instructions for further details.
Performance				
Class Rating	23, 32			ISO 10582
Dimensional Stability	≤ 0.25%			EN 434
Abrasion Rating	Group T			EN 660-1
Residual Indentation	≤0.1mm			EN 433
Furniture Leg	No Damage			EN 424
Castor Chair	No Damage			EN 425
Impact Sound Reduction	Δ Lw = 6dB			EN ISO 717-2
Curl Resistance to Heat	≤ 2mm			EN 434
Thermal Performance (Underfloor heating)	0.07 m2 k/W (suitable – max. 27° C)			EN 12667
Light Fastness	≥6			EN ISO 105-B02
Chemical Resistance	Class 0			EN 423
Electrical Propensity	0.5kV			EN 1815
Slip Resistance	P1, R10			AS/NZ 4586-2013
Commercial Warranty	10 Years			
Residential Warranty	25 Years			
Reaction to Fire	Critical Radiant Flux Smoke Value Bfl-S1	6.1 kW/m2 148 %.min		AS/ISO 9239.1-2003 EN 13501-1
VOC Rating	Available on Request			
Recommended Adhesive	Polymer 265 Adhesive – General application Roberts GS200 – Universal Vinyl Adhesive, Solvent Free, Low VOC, Green Star Compliant Holdfast 416 – Multi Purpose Sheet and Tile Adhesive			

100% Recyclable

Bio-based Plasticisers



