

Resiplank

Aqua Protect Vinyl Floors

Resiplank doesn't trap dirt like many natural and fabric materials. Resiplank is treated with an enhanced surface coating. It also means that the floor does not need to be sealed after installation. The Resiplank surface protection system is built into the Ecotecture technology and provides a hygienic and durable finish that will protect your floor for years to come.

Cleaning after installation

1. Remove all loose debris from the floor using a vacuum, brush or dust mop (if using a vacuum, please check the manufacturer's guidelines to make sure it's suitable for Resiplank).
2. Ensure that all dry adhesive is removed from the surface.
3. Damp mop with a pH neutral detergent or if machine cleaning (no greater than 175rpm) use a 3M red pad (or equivalent) or scrubber dryer to clean the floor.

Routine maintenance

The commercial cleaning and maintenance regime is simple and can be carried out by hand or using mechanical cleaning apparatus.

1. Vacuum, sweep or mop to remove all dust and loose debris (if using a vacuum, please check the manufacturer's guidelines to make sure it's suitable for Resiplank).
2. Damp mop with a neutral detergent or if machine cleaning (no greater than 175rpm) use a 3M red pad (or equivalent) or scrubber dryer to clean the floor.
3. Stubborn stains can be removed by spot cleaning with concentrated neutral detergent and a 3M red pad (or equivalent).



Helpful tips

- Avoid dragging or sliding heavy items of furniture, carousels and point of sale across the floor.
- It is important when designing an installation that the appropriate entrance matting systems are used. Most manufacturers recommend a total of six paces, though this of course is dependent on the application and the space available. At the very least we recommend a non-rubber back matting such as Turtle Mats.
- Mop up spillages quickly to prevent stains.