

NuCore Excellence 12mm Technical Information

	Usage	Result	
	Product Reference	NuCore Excellence	
	Size (L x W x Thickness) mm	2250 x 195 x 12mm	
	Board Type	Drop Loc waxed for moisture resistance	
	Pattern	1 strip- no pattern repeat in length of board	
	Structure	HDF Core E1	
	Edging	Bevelled	
	Pack Size	2.6325 sqm	
	Pack Weight	22kg	
\longrightarrow	Pack Length	2250mm, 6 full length boards per pack	
-%-	Surface finish	EIR registered embossed / matt finish	
0	Environmental Rating	A+. Green Building Council of Australia: Pass	
	Surface Wear Rating	AC4 (Abrasion Class 4) Light Duty Commercial	
Installation Methods			
6	Fully Bonded	No	
T	Nailed	No	
	Floated underlay	Yes	
33333	Over Under Slab Heating	Yes*	
	<u> </u>		

^{*}Subject to compatible subfloor and correct installation (Refer Installation Instructions)

Test Information & Others

	Origin	China
24	Abrasion AS/NZS 4266.20: 2004	AC4 Light Commercial
*	Slip Testing	AS/NZS 4586-2004 Wet: P2, Dry: D1
•	Australian reaction to fire- FLOOR	ASISO 9239-1:2003 CRF 6.3kwm2, smoke value 47%, HF30 value 7.7kw/sqm
•	Australian reaction to fire- WALL	Not applicable
	Burn repairable	No
人	Release of formaldehyde	ASTM D5116 0.008mg/m2/hr (max limit allowable 0.1)
•*	Release of 4-phenylcyclohexene	ASTM D5116 <0.005mg/m2/hr (max limit allowable 0.05)
33333	Total VOC	ASTM D5116 0.005mg/m2/hr (max limit allowable 0.5mg/m2/hr)
命	Warranty- Domestic	25 Year Wear and Lifteime structural
	Warranty- Commercial	5 Year Wear and Lifteime structural

Installation & Warranty

All NuCore floors must be installed by a competent approved installer who will have the necessary skills and take individual site circumstance into account. NuCore warranty will only apply to floors which have been installed according to the NuCore installation instructions available in each box of NuCore and also on the TerraMater website - terramaterfloors.com.au

Please note this technical sheet was written by TerraMater Floors Pty Ltd, All the information is specifield correctly while writing and publication of the sheet. The company reserves the right to change the specifications of this product at any time withour piror notice to third parties.