

## TECHNICAL DATA SHEET

PRODUCT SPECIFICATION		
Width		137mm
Length		1850mm
Pack Size		1.267m <sup>2</sup>
Pallet Size		78.02m <sup>2</sup>
Pack Weight		19kg
Total Thickness		14mm
Surface Coating		UV Cured Acrylic Lacquer
Surface Treatment		Smooth or Brushed
Usage Class	EN 16511	Class 32 AC4

PHYSICAL PROPERTY	TEST METHOD	ARC BAMBOO
Constructions		Solid stranded woven bamboo
Colours in Range		5
Edge Detail		Micro-Bevel 4 sides
Installation Method		Floating
Joining System		Uniclic
<b>Moisture Content</b>		6% - 8% MC
Slip Resistance	AS 4586:2013	P1
Abrasion Group		AC4
Fire Resistance	ASISO 9239.1-2003	5.4 Kw/m2 Smoke 15
Thermal Resistance		R= 0.147
Electric Behavior		Static free
Indoor Air Quality	ASTM D5116	<0.008mg/m2/hr (24 hours)
Warranty	Domestic Use	25 year wear and lifetime structural*
	Commerical Use	Available upon request*

## \*Warranty Details

Arc Bamboo Flooring Warranty Terms and Conditions are available online at <a href="www.premiumfloors.com.au">www.premiumfloors.com.au</a> (in Australia) or www.floorscape.co.nz (in New Zealand) or from an authorised Arc Bamboo Retailer.