

Emission Test Certificate

Wednesday, May 18th, 2016

Supplier: Premium Floors (7/14 Rodborough Road, French's Forest, NSW 2086)

Sample Description: Unilin 12mm Laminate Flooring

Date Tested: May 2016 (Tested by FORAY Laboratories - NATA Accreditation 1231)

Test Method: ASTM D5116 "Standard Guide for Small-Scale Environmental Chamber Determinations of Organic Emissions from Indoor Material/Products".

Emission Data:

Green Building Council of Australia Green Star Design & As Built v1.1 13.1.1	Unilin 12mm Laminate Flooring
Total Volatile Organic Compound Emission Rate	Total Volatile Organic Compound
limit <0.5mg/m ² /hr	Emission Rate: 0.046 mg/m ² /hr
4-phenylcyclohexene Emission Rate limit <0.05mg/m ² /hr	4-phenylcyclohexene Emission Rate: <0.004 mg/m ² /hr
Formaldehyde Emission limit	Formaldehyde Emission:
<0.100 mg/m²/hr	<0.005 mg/m ² /hr

Dr. Vyt Garnys PhD, BSc(Hons) AIMM, ARACI, ISIAQ ACA, AIRAH, FMA Managing Director and Principal Consultant

TRAIL

Tuan Duong PhD, B.E. Chem. Consultant

Nick Joy BSc (Hons) Consultant

CV160516