

Endurance Bamboo

Bamboo flooring is an attractive alternative to hardwood floors. Naturally self-generating, bamboo grows to maturity within five years and is regarded as the strongest plant on earth.



TOPDECK FLOORING

Endurance Bamboo

Endurance bamboo only uses the best flooring techniques in manufacturing our strand woven flooring product. Our waxed edges provide for a superior locking system.

Using wax enables the following benefits:

- Noise suppression in the joints, making for a quieter floor.
- Protecting the joints from accidental water spills, and drying out.
- Quicker easier installation with a better more secure locking fit.

Endurance Bamboo Solid Collection


- Dimensions:
1850mm long X 135mm wide
X 14mm thick
- Licensed Click & Drop (L2C)
- Box contains: 6 Planks = 1.5sqm
Box Weight: 22Kg
- 8 Colours:
 - Lunar White / Semi Gloss
 - Natural / Gloss & Semi Gloss
 - Honey / Semi Gloss
 - Coffee / Gloss & Semi Gloss
 - Mahogany / Gloss
 - Smooth Forest Red / Semi Gloss
 - Smooth Rich Brown / Semi Gloss
 - French Bleed / Semi Gloss




Lunar White




Natural




Honey




Coffee




Mahogany



Forest Red



Rich Brown



French Bleed




Stair Nosing


Endurance Bamboo Engineered Collection




- Dimensions:
1830mm long X 190mm wide
X 3/14mm thick
Semi Gloss Finish
- Box Contains: 6 Planks = 2.0862sqm
Box Weight: 22Kg
- 5G Licensed Lock System




Natural




Honey




Coffee



Forest Red



Rich Brown



Stair Nosing

ENDURANCE BAMBOO SOLID COLLECTION

ENDURANCE BAMBOO ENGINEERED COLLECTION

TECHNICAL SPECIFICATIONS



E0
DIN EN120

ISO9001

ISO14001



INSTALLATION METHOD

Floating Floor

COATING FINISH

9 layers of Treffert water-based polyurethane finish

HARDNESS

Janka 15kn

COLOUR COLLECTION

Lunar White, Natural, Honey Coffee, Mahogany, Forest Red, Rich Brown, French Bleed

FIRE RATING

Critical Heat Flux & Critical Radiant Flux (CHF & CRF) 4.9kw/m²

SLIP RATING

Slip Resistance Value (SRV): 15 (P1) as per Slip Resistance AS 4586 (2013)

ENVIRONMENTAL & QUALITY CERTIFICATES

VOC E0 (0.2Mg/L) Tested in accordance to ISO16000 parts -3 -6 -9 -11 standard
ISO9000 Quality control System and ISO14000 Environment Control System, CE and FSC certificate

STRUCTURAL WARRANTY

25 years residential 10 years commercial

COATING WARRANTY

5 years residential 3 years commercial

Combining quality & environmental control standards throughout the manufacturing process.



As bamboo is a natural product, the colour, grain and feature patterns will vary in the flooring as in the printed media.
For detail maintenance & installation guidelines please refer to the website.





Quality is our Attitude

www.topdeckflooring.com.au

Importer & Supplier of Quality Floor Boards



TOPDECK FLOORING

Topdeck International Pty Ltd

16 Salisbury Street, Silverwater, NSW 2128 Australia

Phone: 02-9748 2288 | Fax: 02-9748 2266

Email: info@topdeckflooring.com.au