

Technical Data

Attributes	Standard	Result
Type of floor covering		Hybrid / Rigid Core
Installation		5G® Click
Core		SPC
Colours		10
Size		1820 x 180 mm
Thickness		7.0 mm
Core thickness		5 mm
Wear layer		0.5 mm
Surface treatment		PU coating
Backing		1.5 mm EVA underlay
Packaging		6 planks / pack = 1.996 m ²
Total weight		10.19 kg/m ² / 20.04 kg per pack
Beveled edge		4 sided micro bevel
Classification	ISO 10874 / EN 685 ISO 10874 / EN 685	Commercial: light Domestic: heavy
Reaction to fire	AS/NZ ISO9239 1-2003	CHF: ≥11 k@/m ² Smoke Value: 136% -min
Slip resistance	AS/NZS 4586.2013 Wet pendulum	SRV 30 / P2
Dimensional stability	Heat at 60 °C for 24 hours	Length: -0.11% Width: -0.09%
Acoustic impact noise reduction	AS/NZ ISO 717.2-2004	F _{LIC} ^{4,5} = 66 L'nTw ³ = 43 AAAC 5 Star Rating
Underfloor heating		Suitable for hydronic underfloor heating, max. 27°C
Environmental	ASTM D5116-17 Green Building Council of Australia Phthalate Free	Compliant for VOC Yes
Warranty	Commercial Domestic	10 years wear 25 years wear

Please refer to Terra Mater Floors warranty information for guidance. www.terramaterfloors.com.au

