



Technical Data

Attributes	Standard	Result
Type of floor covering		Hybrid / Rigid Core
Installation		5G® Click
Core		SPC
Colours		10
Size		1820mm x 225mm
Thickness		9.7mm
Core thickness		7.0mm
Wear layer		0.7mm
Surface treatment		PU coating
Backing		2.0mm EVA underlay
Packaging		4 Planks / pack = 1.638m ²
Total weight		14.71kg/m ² / 24.10kg per pack
Beveled edge		4 sided micro bevel
Classification	ISO 10874 / EN 685 ISO 10874 / EN 685	Commercial: heavy Domestic: very heavy
Reaction to fire	AS/NZ ISO9239 1-2003	CHF: 9.3kW/m ² Smoke value: 207%.min
Slip resistance	AS 4586-2013 Amdt 1-2017 Appendix A	SRV 37 / P3
Dimensional stability	Heat at 60°C for 24 hours	Length: -0.15% Width: -0.15%
Acoustic impact noise reduction	AS/NZ ISO 717.2-2004	FIIC ^{4,5} = 64 L'nTw ³ = 38 AAAC 6 Star Rating ¹
Underfloor heating		Suitable for hydronic underfloor heating, max. 27°C
Environmental	ASTM D5116-17 Green Building Council of Australia Phthalate Free	Compliant for VOC Yes
Quartz content (wt%)		Not detected
Warranty	Commercial Domestic	15 Year wear* 30 Year wear*

*Please refer to Terra Mater warranty information for guidance. www.terramaterfloors.com.au

¹Please refer to www.terramaterfloors.com.au for results.



Terra Mater

23-27 Rodeo Drive, Dandenong South VIC 3175 Australia | 1300 671 777 | sales@terramaterfloors.com.au | www.terramaterfloors.com.au